

PIT js2 bc

401101



PITjog manually operated control device, 2 installed pushbuttons (each N/C / N/O) and 1 blind plug, connection via 10-pin coiled cable with open end, cable length: 5 m.

Technical details

General data

Approval: CE

Self-monitored: no

Technical data

Electrical data

Supply voltage (V): 24 - 24 V

Type of supply voltage U1: AC/DC

Push button

Number, pushbutton: 2

Relay outputs

Voltage DC1 safety cont.: 24 V

Environmental data

Ambient temperature: -10 - 55 °C

Mechanical data

Length cable: 5 m

Material of cable insulation 1: PUR

Conductor cross section: 0.14 - 0.14 mm²

Housing material: PC-ABS-Blend UL 94V0

Height dimension: 341 mm

Width dimension: 75 mm

Depth dimension:	60 mm
Net weight:	823 g
Gross weight:	923 g
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	yes
RoHS except.s acc. to direct.:	6c
REACH compliance:	contains min. 1 SVHC-substance
REACH included substances:	Lead
%-part of the pollutant:	> 0,1
CAS No.:	7439-92-1
WEEE classification (08/2018):	5 devices (feed size < 50cm)
Commercial data	
ECLASS version:	ECLASS-9.1
ECLASS Reference Feature:	27371244
ETIM Version:	ETIM-7.0
ETIM Reference Group:	EG000017
ETIM Reference Feature:	EC002034