

PNOZ m B1

772101



Configurable safe small controllers PNOZmulti 2 base unit, expandable, Ethernet interface with switch, USB 20 memory.

Technical details

General data

Approval:	CE, UKCA, cULus Listed, KOSHA, TÜV, EAC (Eurasian)
Application range:	Failsafe

Technical data

Electrical data

Purpose of U1:	System supply
Supply voltage (V):	24 - 24 V
Type of supply voltage U1:	DC
Power consumption DC:	18.5 W

Test clock outputs

Number of test pulse outputs:	4
-------------------------------	---

Ethernet interface

Ethernet IP address:	169.254.60.1
Connector type ETHERNET int.:	RJ45
Ethernet transmission rate:	10 MBit/s, 100 MBit/s

CANopen interface

Number of Ethernet interfaces:	2
--------------------------------	---


Environmental data

Ambient temperature standard:	EN 60068-2-14
Ambient temperature:	0 - 60 °C

Storage temperature standard:	EN 60068-2-1/-2
Climatic suitability standard:	EN 60068-2-30, EN 60068-2-78
Humidity rating:	93 % r. h. at 40 °C
Condensation permitted?:	Not permitted
Perm. operating height ASL:	2000 m
EMC to standard ...:	EN 61131-2
Vibration to standard ...:	EN 60068-2-6
Clearance & creepage dist. to:	EN 61131-2
Overvoltage category:	II
Pollution degree clear.&creep.:	2
Protection type standard:	EN 60529
Mechanical data	
Mounting position:	horizontal on top hat rail
DIN-rail dimensions:	35 x 7.5 EN 50022
Housing material lower section:	PC
Housing material front plate:	PC
Housing material upper part:	PC
Connection terminal:	Screw terminal, Cage clamp terminal
Terminal style:	plug-in
Flex. cond. c/s AWG info:	24 - 12 AWG
Height dimension:	101.4 mm
Width dimension:	45 mm
Depth dimension:	120.2 mm
Net weight:	209 g
Gross weight:	219 g
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	yes

RoHS except.s acc. to direct.:	7a
REACH compliance:	contains min. 1 SVHC-substance
REACH included substances:	Lead
%-part of the pollutant:	> 0,1 %
CAS No.:	7439-92-1
WEEE classifikation (08/2018):	5 devices (feed size < 50cm)
Commercial data	
ECLASS version:	ECLASS-9.1
ECLASS Reference Feature:	27242207
ETIM Version:	ETIM-7.0
ETIM Reference Group:	EG000024
ETIM Reference Feature:	EC000236

Obligatory accessories



773010B

Basic Licence for PNOZmulti Config.



750016


Set4 Screw Terminals



751016

Set4 Spring Terminals

Optional accessories



773011B

Basic Licence for PNOZmulti Service

779213

USB Memory 512MB



773011K

User Licence for PNOZmulti Service




380401

RJ45 Connector



773010K

User Licence for PNOZmulti Config




773011U

Basic Upgr Licence for PNOZmulti Service



773011V

User Upgr Licence for PNOZmulti Service



773010U

Basic Upgr Licence for PNOZmulti Config

